
SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

COMPANY IDENTIFICATION

FULBAT S.a.s

23 bis rue Edouard Nieuport - 92150 SURESNES - FRANCE

Tel: +33 1 83 62 45 60

Web: <http://www.fulbat.com>

Product Identification

Product Name: Lithion-ion Rechargeable Battery (UN 3480)

Chemical System: Lithium-ion

FLTZ5S ; FLTZ7S ; FLTX7L ; FLT9B ; FLTX9 ; FLTZ10S ; FLT12B ; FLTX12 ; FLTX14H ;

FLTZ14S ; FLTX20H ; FLTX20HL.

2. COMPOSITION / INFORMATION ON INGREDIENTS

IMPORTANT NOTE: The battery cell should not be opened or exposed to heat because exposure to the following ingredients contained within could be harmful under some circumstances.

Component	CAS No.	Weight
Lithium Iron Phosphate	15365-14-7	32.5%
Polyvinylidene Fluoride(PVDF)	24937-79-9	2.60%
Aluminium(Al)	7429-90-5	8.10%
Graphite	7782-42-5	16.45%
Styrene-Butadiene Rubber(SBR)	9003-55-8	0.45%
Carboxymethyl cellulose	9000-11-7	0.35%
Copper (Cu)	7440-50-8	15.60%
Lithium Hexafluorophosphate	21324-40-3	16.45%
Polyethylene	9002-88-4	6.75%
Ethylene-Propylene-Diene Monomer	24937-16-4	0.75%

Weight % listed is based on approximate percent of the average weight of the battery

3. HAZARDS IDENTIFICATION

The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation. Fulbat S.a.s makes no warranty, expressed or implied, with respect to this information and disclaims all liabilities from reliance on it.

For the battery cell, chemical materials are stored in a hermetically sealed Aluminum laminated case, designed to withstand temperatures and pressures encountered during normal use. As a result, during normal use, there is no physical danger of ignition or explosion and chemical danger of hazardous materials' leakage.

However, if exposed to a fire, added mechanical shocks, decomposed, added electric stress by miss-use, the gas release vent will be operated. The battery cell case will be breached at the extreme, hazardous materials may be released.

Moreover, if heated strongly by the surrounding fire, acrid gas may be emitted. Most important hazard and effects

Human health effects:

Inhalation: The steam of the electrolyte has an anesthesia action and stimulates a respiratory tract.

Skin contact: The steam of the electrolyte stimulates a skin. The electrolyte skin contact causes a sore and a stimulation on the skin.

Eye contact: The steam of the electrolyte stimulates eyes. The electrolyte eye contact causes a sore and a stimulation on the eye. Especially, substance that causes a strong inflammation of the eyes is contained.

Environmental effects: Since a battery cell remains in the environment, do not throw out it into the environment.

Specific hazards:

If the electrolyte contacts with water, it will generate detrimental hydrogen fluoride. Since the leaked electrolyte is inflammable liquid, do not bring close to fire.

4. FIRST-AID MEASURES

Spilled internal cell materials

Inhalation:

Make the victim blow his/her nose, gargle. Seek medical attention if necessary.

Skin contact:

Remove contaminated clothes and shoes immediately. Wash extraneous matter or contact region with soap and plenty of water immediately.

Eye contact:

Do not rub one's eyes. Immediately flush eyes with water continuously for at least 15 minutes. Seek medical attention immediately.

A battery cell and spilled internal cell materials

Ingestion:

Make the victim vomit. When it is impossible or the feeling is not well after vomiting, seek medical attention.

5. FIRE-FIGHTING MEASURE

Suitable extinguishing media: Plenty of water, carbon dioxide gas, nitrogen gas, chemical powder fire extinguishing medium and fire foam.

The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation. Fulbat S.a.s makes no warranty, expressed or implied, with respect to this information and disclaims all liabilities from reliance on it.

•Specific hazards: Corrosive gas may be emitted during fire.

•Specific methods of fire-fighting: When the battery burns with other combustibles simultaneously, take fireextinguishing method which correspond to the combustibles. Extinguish a fire from the windward as much as possible.

•Special protective equipment for firefighters:

Respiratory protection: Respiratory equipment of a gas cylinder style or protection-against-dust mask.

Hand protection: Protective gloves

Eye protection: Goggle or protective glasses designed to protect against liquid splashes

Skin and body protection: Protective cloth

6. ACCIDENTAL RELEASE MEASURES

Spilled internal cell materials, such as electrolyte leaked from a battery cell, are carefully dealt with according to the followings.

•Precautions for human body:

Remove spilled materials with protective equipment (protective glasses and protective gloves).

Do not inhale the gas as much as possible. Moreover, avoid touching as much as possible.

•Environmental precautions: Do not throw out into the environment.

•Method of cleaning up:

The spilled solids are put into a container. The leaked place is wiped off with dry cloth.

•Prevention of secondary hazards:

Avoid re-scattering. Do not bring the collected materials close to fire.

7. HANDLING AND STORAGE

•Handling

Technical measures

Prevention of user exposure: Not necessary under normal use.

Prevention of fire and explosion: Not necessary under normal use.

Precaution for safe handling: Do not damage or remove the external tube.

Specific safe handling advice:

Never throw out cells in a fire or expose to high temperatures. Do not soak cells in water or seawater. Do not expose to strong oxidizers. Do not give a strong mechanical shock or fling. Never disassemble, modify or deform. Do not connect the positive terminal to the negative terminal with electrically conductive material. In the case of charging, use only dedicated charger or charge according to the conditions specified by Fulbat.

•Storage

Technical measures

Storage conditions (suitable, to be avoid): Avoid direct sunlight, high temperature, high humidity.

Store in cool place (temperature: -20 ~ 35 degree C, humidity: 45 ~ 85%).

Incompatible products: Conductive materials, water, seawater, strong oxidizers and strong acids

Packing material (recommended, not suitable): Insulative and tearproof materials are recommended.

The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation. Fulbat S.a.s makes no warranty, expressed or implied, with respect to this information and disclaims all liabilities from reliance on it.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

•Control parameters:

Not established

•Appropriate engineering controls

Under normal conditions (during discharge) release of ingredients does not occur.

ACGIH: American Conference of Governmental Industrial Hygienists ,Inc.

TLV-TWA: Threshold Limit Value-Time Weighted Average concentration

BEI: Biological Exposure Indices

•Personal protective equipment

Respiratory protection: Respirator with air cylinder, dust mask

Hand protection: Protective gloves

Eye protection: Goggle or protective glasses designed to protect against liquid splashes

Skin and body protection: Working clothes with long sleeve and long trousers

9. PHYSICAL AND CHEMICAL PROPERTIES

•Appearance

Physical state: Solid

Form: Prismatic

Color: Metallic color (without tube)

Odor: No odor

pH: NA

•Specific temperatures/temperature ranges at which changes in physical state occur:

There is no useful information for the product as a mixture.

•Flash point: NA

•Explosion properties: NA

•Density: NA

•Solubility ,with indication of the solvent(s): Insoluble in water

10. STABILITY AND REACTIVITY

- Stability: Stable under normal use
 - Hazardous reactions occurring under specific conditions
 - Conditions to avoid: When a battery cell is exposed to an external short-circuit, crushes, deformation, high temperature above 100°C, it will be the cause of heat generation and ignition. Do not put it under sunlight and high humidity directly.
 - Materials to avoid: Conductive materials, water, seawater, strong oxidizers and strong acids.
 - Hazardous decomposition products: Acrid or harmful gas is emitted during fire.
-

11. TOXICOLOGICAL INFORMATION

There is no available data on the product itself. The information of the internal cell materials is as follows.

Lithium cobaltate – LiFePO₄

- Acute toxicity: No applicable data.
- Local effects: Unknown.
- Sensitization: The nervous system of respiratory organs may be stimulated sensitively.
- Chronic toxicity/Long term toxicity: No applicable data.
- Skin causticity: Although it is very rare, the rash of the skin and allergic erythema may result.

Aluminum

- Local effects: Aluminum itself has no toxicity. When it goes into a wound, dermatitis may be caused.
- Chronic toxicity/Long term toxicity: By the long-term inhalation of coarse particulate or fume, it is possible to cause a lung damage (aluminum lungs).

Graphite

- Acute toxicity: Unknown.
- Local effects: When it goes into one's eyes, it stimulates one's eyes; conjunctivitis, thickening of corneal epithelium or edematous inflammation palpebra may be caused.
- Chronic toxicity/Long term toxicity: Since the long-term inhalation of high levels of graphite coarse particulate may become a cause of a lung disease or a tracheal disease.
- Carcinogenicity: Graphite is not recognized as a cause of cancer by research organizations and natural toxic substance research organizations of cancer.

Copper

- Acute toxicity: 60-100mg sized coarse particulate causes a gastrointestinal disturbance with nausea and inflammation. TDLo, hypodermic - Rabbit 375mg/kg
- Local effects: Coarse particulate stimulates a nose and a tracheal. When it goes into one's eyes, the symptom of the reddening and the pain is caused.
- Sensitization: Sensitization of the skin may be caused by long-term or repetitive contact.

The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation. Fulbat S.a.s makes no warranty, expressed or implied, with respect to this information and disclaims all liabilities from reliance on it.

- Reproductive effects: TDLo, oral - Rat 152mg/kg

Organic Electrolyte

- Acute toxicity: LD50, oral - Rat 2,000mg/kg or more
- Local effects: Unknown.
- Skin irritation study: Rabbit – Mild
- eye irritation study: Rabbit - Very severe

12. ECOLOGICAL INFORMATION

- Persistence/degradability: do not bury or throw out into the environment.

13. DISPOSAL CONSIDERATIONS

- Recommended methods for safe and environmentally preferred disposal:

Product(waste from residues)

Do not throw out a used battery cell. Recycle it through the recycling company.

Contaminated packaging

Neither a container nor packing is contaminated during normal use. When internal materials leaked from a battery cell contaminates, dispose as industrial wastes subject to special control.

14. TRANSPORT INFORMATION

In the case of transportation, avoid exposure to high temperature and prevent the formation of any condensation. Take in a cargo of them without falling, dropping and breakage. Prevent collapse of cargo piles and wet by rain. The container must be handled carefully. Do not give shocks that result in a mark of hitting on a cell. Please refer to Section 7-HANDLING AND STORAGE also.

- UN classification: However this product's shipping name is "Lithium batteries" (or "Lithium Batteries packed with equipment" or "Lithium Batteries contained in equipment"), it is not recognized as "DANGEROUS GOODS" when its transport condition accords with "packing instructions 965 section II of IATA-DGR" (or "packing instructions 966 section II" or "packing instructions 967 section II") or "special provision 188 of IMO-IMDG Code". (UN 3480)

15. REGULATORY INFORMATION

《Classification, Labeling and Packaging Regulation》

《REACH (EC)1907/2006》

《Dangerous Goods Regulation》

《Recommendations on Transport of Dangerous Goods Model Regulations》

《International Maritime Dangerous Goods》

《Technical Instructions for the Safe Transport of Dangerous Goods》

《Classification and code of dangerous goods》

《Occupational Safety and Health Act》 (OSHA)

《Toxic Substances Control Act》 (TSCA)

The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation. Fulbat S.a.s makes no warranty, expressed or implied, with respect to this information and disclaims all liabilities from reliance on it.

《Consumer Product Safety Act》(CPSA)
《Federal Environmental Pollution Control Act》(FEPCA)
《The Oil Pollution Act》(OPA)
《Resource Conservation and Recovery Act》(RCRA)
《Safety Drinking Water Act》(CWA)
《Code of Federal Regulations》(CFR)

In accordance with all Federal, State and local laws

16. OTHER INFORMATION

- The information contained in this Safety data sheet is based on the present state of knowledge and current legislation.
- This safety data sheet provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.
- Reference

Chemical substances information: Japan Advanced Information center of Safety and Health
International Chemical Safety Cards (ICSCs):

International Occupational Safety and Health Information Centre (CIS)

2002 TLVs and BEIs: American Conference of Governmental Industrial Hygienists (ACGIH) New
Dangerous Goods Best Practice 008--in the 51st Edition IATA DGR(2010)(with effect from 01
January 2010)

GB/T 16483-2008 Safety data sheet for chemical products Content and order of sections

ISO 11014:2009(E) Safety data sheet for chemical products –Content and order of sections

IMDG Code – 2008 Edition: International Maritime Organization (IMO)

RTECS(CD-ROM)

MSDS of raw materials prepared by the manufactures

First edition : Feb. 05 2016

Latest edition :Apr. 14 .2018

Prepared and approved by Fulbat S.a.s

The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation. Fulbat S.a.s makes no warranty, expressed or implied, with respect to this information and disclaims all liabilities from reliance on it.